



Chain		Pitch	Inner width	Inner link width	Outer plate width	Bushing Ø	Pin Ø	Width over pin	Projection over connecting link	Plate thickness	Plate height	Bearing area	Breaking load DIN	Weight	Connecting links
⚙		p	b ₁ min.	b ₂ max.	b ₃ min.	d ₁ max.	d ₂ max.	l ₁ max.	k max.	s	g max.	f	F _B min.	q ≈	Nr.
No.	Ind.	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	cm ²	kN	kg/m	
200	²⁶	15,0	14,0	18,50	19,00	9,0	6,0	26,0	2,0	2,00	14,0	1,1	12,5	1,25	111,12
203	²⁶	20,0	16,0	22,50	23,00	12,0	8,0	33,0	3,0	3,00	19,0	1,8	25,0	2,10	111,11,12
206	²⁶	25,0	18,0	24,50	25,00	15,0	10,0	37,0	3,5	3,00	24,0	2,5	31,5	2,60	111,12
209	²⁶	30,0	20,0	28,50	29,00	17,0	11,0	43,0	3,5	4,00	28,0	3,1	40,0	4,00	111,12
212	²⁶	35,0	22,0	30,50	31,00	18,0	12,0	46,0	4,5	4,00	30,0	3,7	50,0	4,30	111,12
215	²⁶	40,0	25,0	35,50	36,00	20,0	14,0	53,0	4,5	5,00	35,0	5,0	63,0	6,00	111,12
218	²⁶	45,0	30,0	42,50	43,00	22,0	16,0	63,0	4,5	6,00	40,0	6,8	80,0	8,00	111,12
221	²⁶	50,0	35,0	47,50	48,00	26,0	18,0	68,0	6,0	6,00	44,00	8,6	100,0	9,00	111,12
222	²⁶	55,0	45,0	61,50	62,50	30,0	20,0	86,0	7,0	8,00	49,00	12,3	125,0	13,60	111,12
223	²⁶	60,0	50,0	66,50	67,50	32,0	22,0	93,0	7,0	8,00	55,00	14,6	160,0	14,90	111,12
224	²⁶	65,0	55,0	72,00	73,00	36,0	26,0	98,0	8,0	8,00	61,00	18,7	200,0	18,90	111,12
225	²⁶	70,0	65,0	86,00	87,00	42,0	30,0	117,0	8,0	10,00	67,00	25,8	250,0	24,70	111,12

²⁶ Connecting link No. 111 (S) with double cottered pin, i.e. projection k on both chain sides

For details on orders and enquiries see page 148. Sprockets on request.

Chain speeds with bush chains up to a pitch:

- of 20 mm ... up to 5 m/s
- of 40 mm ... up to 4 m/s
- more than 40 mm ... up to 3 m/s

Connecting links: According to ISO (...)



No. 4 (B)
Inner link



No. 7 (A)
Outer link
(to be riveted)



No. 11 (E)
Spring clip
connecting link



No. 111 (S)
Connecting link
with cottered pin



No. 12 (L)
Single
cranked link